400 Series

Creating a model number

Model Type
(blank) - Standard Frame
HD - - - Gusseted Frame

(blank) - Standard finishes
C - - - - Clean Room finishes
N - - - - Electroless Nickel Plate

ESD Ground
(blank) - No ESD Ground
E - - - - Ground Lug and Drag Chain for use in EPA's

Style
410 - Single Main Beam
425 - Triple Main Beam with Gearbox (available only with HD frame)

Gearbox
(blank) - Standard 713 Gearbox
715 - - - Upgrade to 715 Gearbox

Push Bar
(blank) – No Push Bar
P1 - - - - Gearbox mounted Push Bar

Trunnion Interface Mounts
0000 – No Clamp
1018 – Mounting Plate
1023 – Board Clamp (except N & C option)
SA10 – Angle Clamp

Lubricants:
(blank) - Standard lubricant
L1 - - - - Trunnions & caster swivel bearings lubricated with Krytox GPL 207
L2 - - - - Trunnions & caster swivel bearings lubricated with Braycote 601EF
NOTE:
"C" finish includes L1 Lubricants

Proof Load Test
(blank) - No Proof Load Test
PLT - - - Standard Proof Load Test (includes deliverable report)

Caster
5 - - - - - (standard on 410 style) Series 1 caster with Performa wheel & Side Lock brake (Except C & N Finish)
C5SPX - (Standard on 425 style) Series 2 caster with Performa wheel and Tech Lock brake
C5TL - - Series 2 casters with Total Lock brake and polyurethane wheel (except C & N Finish)
C5EX - - Series 2 casters with conductive wheel and Side Lock brake (except C & N Finish)

Main Beam
B"XXX"- Main Beam length where "XXX"= length in inches between trunnion interface mounts. 26" minimum, 104" maximum, 1" increments
TB - - - - -Standard 72" to 120" Telescopic Main Beam for 66" to 104" maximum part length

Index Plate
(blank)- - - - No Index Plate
IND15 - - - -15° Index Plate
INDS15 - - -15° Index Plate with Index Stops on Gearbox end only

Examples:

HD 425 - 1018 - B 048 - C5EX

- **HD** – Gusseted frame
- **425** – Triple beam with gearbox
- **1018** – Mounting plate interface
- **B 048** – Inside Length between trunnion mounts is 48" max
- **C5EX** – Series 2 caster with conductive wheel and brake.

410 - 1023 - IND15 - B072 - 5

- **410** – Standard frame
- **1023** – Single beam with gearbox
- **IND15** – Board clamp
- **B072** – 15° index plate
- **5** – Inside Length between trunnion mounts 72" max