




Small Satellite Fixture

Creating a model number



Finishes
 (blank) - Standard finishes (no zinc)
C - - - - - Clean room finishes

ESD Ground
 (blank) - No ESD ground
E - - - - - Ground lug and drag chain for use in EPA's

Size
36 - - - 36" Primary axis centerline to floor height
48 - - - 48" Primary axis centerline to floor height
60 - - - 60" Primary axis centerline to floor height
AH - - -30" to 60" Adjustable centerline to floor height

Primary Axis Gearbox
 (blank) – Standard 60:1 ratio gearbox
DR3 - - - 300:1 ratio gearbox (Must select "D" option)

Cordless Drill Drive Input
 (blank) – No drill drive (hand crank only)
D - - - - - Battery powered right angle drill permanently mounted to gearbox input shaft. (Must select DR3 gearbox option)

Primary Axis Index plate
 (blank) – No index plate on primary axis
IND30 – 30° Index plate on primary input (Must select AH option)

Secondary Axis Index plate
 (blank) – No index plate on secondary axis
SAIND30 Secondary axis of rotation index plate (Must select SA option)

Payload Interface
P24 - - - Standard Ø24" circular interface plate 20X through holes for 1/2" fasteners on Ø22" bolt circle

Proof Load Test
 (blank) - - No proof load test
PLT - - - - Standard proof load test (includes deliverable report)

Secondary Axis of Rotation Structure
 (blank) - No secondary axis of rotation
SA1 - - - - Secondary axis of rotation (Bolt Position 1)
SA2 - - - - Secondary axis of rotation (Bolt Position 2)
SA3 - - - - Secondary axis of rotation (Bolt Position 3)
SA4 - - - - Secondary axis of rotation (Bolt Position 4)
SA5 - - - - Secondary axis of rotation (Bolt Position 5)
SA6 - - - - Secondary axis of rotation (Bolt Position 6)
NOTE: See proposal drawing to determine correct bolt position. Bolt positions can be changed in the field, but bolt position selected will be the bolt position fixture is shipped with. SA1-SA4 not available with CTL-36 size.

Toolbox
 (blank) - No storage toolbox
BX - - - Storage toolbox included

Towing Interface
 (blank) - No tow bar
T1 - - - - Tow bar included

Lubricants:
 (blank) - Standard lubricant
L1 - - - - Caster swivel bearings lubricated with Krytox GPL 207
L2 - - - - Caster swivel bearings lubricated with Braycote 601EF
NOTE: "C" finish includes L1 lubricants

Caster
C6 - - - Ø6" x 3" Heavy duty nylon wheel caster with brakes and swivel locks
C8 - - - Ø8" x 2 1/2" Heavy duty nylon wheel caster with brakes and swivel locks

Example:

