




## 500 Series

Creating a model number



### Model Type

Gusseted Frame

- (blank)-Standard finishes
- C** - - - - Clean Room finishes  
Except Hydraulic
- N** - - - - Electroless Nickel Plate

### ESD Ground

- (blank) - No ESD Ground
- E** - - - - Ground Lug and Drag  
Chain for use in EPA's

### Style

- 510** - Single Beam with Gearbox
- 525** - Triple Beam with Gearbox

### Riser Adjustment

- (blank) - Standard pinned Risers
- HYD** - - Hydraulic adjustment  
(HD510 style only)

### Gearbox

- (blank)- Standard 713 Gearbox  
on HD510HYD or  
Standard 715 Gearbox  
On HD510 and HD525
- 715** - - - - Optional 715 Gearbox on  
HD510HYD
- LGB** - - Less Gearbox

### Push Bar

- (blank) - No Push Bar
- P1** - - - - Gearbox mounted Push Bar

### Trunnion Interface Mounts

- 0000** - No Clamp
- 1018** - Mounting Plate
- 1023** - Board Clamp  
(except N & C option)
- SA10** - Angle Clamp

### Lubricants:

- (blank) - Standard lubricant
- L1** - - - - Trunnions & caster swivel  
bearings lubricated with  
Krytox GPL 207
- L2** - - - - Trunnions & caster swivel  
bearings lubricated with  
Braycote 601EF

NOTE:  
"C" finish includes L1 Lubricants

### Proof Load Test

- (blank) - No Proof Load Test
- PLT** - - - - Standard Proof Load Test  
(includes deliverable report)

### Caster

- HD510HYD only**
  - C5SPX** - Standard Series 2 caster with  
Performa wheel and Tech Lock brake
  - C5TL** - - Series 2 casters with Total Lock brake  
and polyurethane wheel
  - C5EX** - - Series 2 casters with conductive wheel  
and Side Lock brake
- HD510  
HD525 only**
  - (blank) - Series 4 caster with polyurethane wheel  
and Tech Lock brake
  - C1** - - - - Series 4 heavy duty caster with Tread Lock  
brake and swivel lock
  - C2** - - - - Standard caster with brake and  
conductive wheels.

### Main Beam

- B"XXX"**- Main Beam length where "XXX"=  
length in inches between trunnion interface  
mounts. 26" minimum, 104" maximum,  
1" increments
- TB** - - - - Standard 72" to 120" Telescopic Main Beam  
for 66" to 104" maximum part length

### Index Plate

- (blank) - - - - No Index Plate
- IND15** - - - Standard 15° Index Plate
- INDS15** - - 15° Index Plate with Index Stops  
on Gearbox end only

### Examples:

