




SFP-1000 Series
Creating a model number

SFP-1000 Series
Creating a model number



Finishes

(blank) - Standard finishes
C - - - - - Clean Room finishes

ESD Ground

(blank) - No ESD Ground
E - - - - - Ground Lug and Drag Chain for use in EPA's

Lubricants

(blank) - Standard lubricants
L1 - - - - - Trunnions, caster swivel bearings, and jacks (if applicable) lubricated with Krytox GPL 207
L2 - - - - - Trunnions, caster swivel bearings, and jacks (if applicable) lubricated with Braycote 601EF
NOTE: "C" finish includes L1 Lubricants

Size

1074 - - 74" Wide frame
1084 - - 84" Wide frame

Jacks

(blank) - No provision for Jacks
J2 - - - - - Jacks Frame mounted with Standard Leveling Foot
J3 - - - - - Jacks Frame mounted with Leveling Foot "F1"

Gearbox

(blank) - - - 1200:1 Low Backlash, non-backdriving Gearbox

Push Bar

(blank) - No Push Bar
P1 - - - - - End Frame-mounted Push Bar

Cordless Hand Drill Input

(blank) - - - No hand drill
D - - - - - - - Battery powered hand drill mounted to gearbox drop down input shaft

Proof Load Test

(blank) - - No Proof Load Test
PLT - - - - - Standard Proof Load Test (includes deliverable report)

Caster

(blank) - Ø8" Nylon caster with brake & swivel lock

Towing Interface

(blank) - No Towing Interface
T1 - - - - - Removable Lunette Ring Towing Interface (attaches to main beam)
T2 - - - - - Removable Ball Coupler Towing Interface (attaches to main beam)
T3 - - - - - Removable Tow Bar (attaches to end frames)

Interface Distance

B"XXX" - - Interface distance where "XXX" = length in inches between trunnion interface mounts. (1" increments within the following range)

MODEL	MIN	MAX
1074	35"	415
1084	35"	415

Trunnion Interface Mounts

P15 - - - - - 11" x 15" Mounting Plate
NOTE: Special Interface mounts available upon request.

Index Plate

IND15 - - - 15° Index Plate
INDS15 - - - 15° Index Plate with Index Stops
NOTE: Special index plate hole spacing available upon request.

Example:

